

Digital multimeter

- Non-contact AC Voltage Detection
- Mini size, portable
- Backlit LCD Display



CE  **CAT III 600V**



Model	DM95	DM95C	DM95A	Accuracy
DC Voltage	200mV/2V/20V/200V/600V	200mV/2V/20V/200V/600V	4V/40V/400V/600V	± (0.5%+2)
AC Voltage	200V/600V	200V/600V	4V/40V/400V/600V	± (1.2%+10)
DC Current	2000uA/200mA/10A	2000uA/200mA/10A	40mA/400mA/10A	± (1.5%+2)
AC Current	-	-	40mA/400mA/10A	± (3.0%+2)
Resistance	200Ω/2kΩ/20kΩ/200kΩ/20MΩ	200Ω/2kΩ/20kΩ/200kΩ/20MΩ	400Ω/4kΩ/40kΩ/400kΩ/40MΩ	± (1.0%+2)
Continuity/ Diode Check	Auto check Continuity or Diode	Auto check Continuity or Diode	Auto check Continuity or Diode	± (1.2%+3)
Non-contact AC Voltage Detection	Yes	Yes	Yes	± (0.8%+3)
Battery Voltage Testing	1.5V/9V	-	-	-
°C/°F	-	-20°C~1000°C/-4°F~1832°F	-20°C~1000°C/-4°F~1832°F	± (1.0%+3)

Feature

Display	2000 Counts	2000 Counts	4000 Counts	
Manual/Auto Range	Manual	Manual	Auto Range	
Auto Power off	√	√	√	
Data Hold	√	√	√	
°C/°F	-	√	√	

General

Batteries	2×1.5V AAA
Size	150×70×50(mm)
Weight	About 195g
Safety Level	EN61010-2-033, CAT III 600V
Accessories	Multimeter-Probe-Batteries-User Manual-Color Box