

## **Data sheet for SINUMERIK Operator panel front**

**MLFB-Ordering data** 

6FC5203-0AF04-0AA0



Figure similar

Client order no. :	Item no. :
Order no. :	Consignment no.
Offer no. :	Project :

Remarks :		noject.	
Screen		Ambient conditions	
Screen diagonal	10 in TFT color VGA		
Screen resolution	640 x 480 Pixel	Climate class according to EN60721-3-3	Condensation and icing excluded. Low air temperature 0 °C (32 °F).
Rated data			
Input voltage	DC 5 V	Ambient temperature	
	Via PCU or TCU	Operation on the front	0 45 °C
		Operation at the rear	0 55 °C
Power consumption		Storage	-20 55 °C
Maximum	16 W	Transport	-20 55 °C
Standard	10 W	_ Relative humidity	
Mechanical data		Operation	5 95 %
Net weight	5.50 kg	Storage	5 95 %
Width	310.0 mm	Transport	5 95 %
Height	330.0 mm		
Depth	45.0 mm	Approvals	
	Without USB protective cover on the front	Certificate of suitability	CE / cULus
Installation depth			
without PCU	35.0 mm		
with PCU 50	120.0 mm		
	Clearance + 10 mm (0.39 in)		
Degree of protection			

IP54 IP00

285.0 mm

304.0 mm

Front side

Rear side

**Mounting surface** 

**Cutout width** 

**Cutout height**